Product Information Sheet

and rounded to the second dec-

Height

Width

Depth

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:				
Supplier's address: Boriana Ltd,	Treti Mart 12, 5370	Dryanovo Gabrovo, BG		
Model identifier: DIR2027-PCB				
Type of light source:				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	Type Y			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
	Product para	meters		
Parameter	Value	Parameter	Value	
	General product	parameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	18	Energy efficiency class	F	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode power (P _{on}), ex- pressed in W	17,6	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W	-	Colour rendering in- dex, rounded to the	80	

200

200

30

nearest integer, or the range of CRI-val-

ues that can be set

Spectral power dis-

range 250 nm to 800

nm, at full-load

in the

tribution

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,457	
		nates (x and y)	0,410	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	5	Survival factor	1,00	
the lumen maintenance factor	0,97			

(a)'-': not applicable; (b)'-': not applicable;

