## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name o	or trade mark:	ULTRALUX
------------	--------	----------------	----------

Supplier's address: Boriana Ltd, Treti Mart 12, 5370 Dryanovo Gabrovo, BG

Model identifier: SPZ15050-PCB

_	•			
Type	Λt	light	COLL	rca.
IVDE	VI.	HEILL	SOU	LC.

Type of light 30	arcc.			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap	Light source cap-type			
(or other electri	(or other electric interface)			
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	High luminance light source:			
Anti-glare shield	d:	No	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		132	Energy efficiency class	В
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		27 900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	5 000
On-mode power (P <sub>on</sub> ), ex- pressed in W		132,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	400	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image
sions without	Width	370		in last page
separate con- trol gear, light- ing control	Depth	57		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,342		
		nates (x and y)	0,349		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	5	Survival factor	1,00		
the lumen maintenance factor	0,98				

(a)'-': not applicable; (b)'-': not applicable;