## **Product Information Sheet**

separate con-

trol gear, light-

control

ing

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	ELEGATED REGUI	-AHON (EU) 2019/2	015 with regard to energ	gy labelling of light
Supplier's name	e or trade mark:	ULTRALUX		
Supplier's addre	ess: Boriana Ltd,	Treti Mart 12, 5370	Dryanovo Gabrovo, BG	
Model identifie	r: LBL52740LV			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		E27		
(or other electri	ic interface)			
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
Energy consurmode (kWh/10 up to the neare	00 h), rounded	5	Energy efficiency class	F
dicating if it refe a sphere (360°)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P <sub>on</sub> ), ex- pressed in W		5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without	Height	80	Spectral power distribution in the	See image in last page
SIGIIS WILLIOUL	Width	45	Tanbadon in the	iii iast page

45

range 250 nm to 800

nm, at full-load

parts and non- lighting con- trol parts, if any (millime- tre)							
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	42				
		Chromaticity coordi-	0,380				
		nates (x and y)	0,380				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	5	Survival factor	0,90				
the lumen maintenance factor	0,93						

(a)'-': not applicable; (b)'-': not applicable;

