## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Boriana Ltd, Treti Mart 12, 5370 Dryanovo Gabrovo, BG

Model identifier: LLV2040-PCB

| Lighting technology used:     | LED    | Non-directional or | NDLS |  |  |  |
|-------------------------------|--------|--------------------|------|--|--|--|
|                               |        | directional:       |      |  |  |  |
| Light source cap-type         | TYPE Y |                    |      |  |  |  |
| (or other electric interface) |        |                    |      |  |  |  |
| Mains or non-mains:           | NMLS   | Connected light    | No   |  |  |  |
|                               |        | source (CLS):      |      |  |  |  |
| Colour-tuneable light source: | No     | Envelope:          | -    |  |  |  |
| High luminance light source:  | No     |                    |      |  |  |  |
| Anti-glare shield:            | No     | Dimmable:          | No   |  |  |  |
|                               |        |                    |      |  |  |  |

## **Product parameters**

| Froduct parameters                                |  |                           |  |              |  |  |  |
|---|--|---------------------------|--|--------------|--|--|--|
| Parameter   |  | Value                     | Parameter  | Value        |  |  |  |
| General product parameters:                       |  |                           |  |              |  |  |  |
|   | mption in on-<br>00 h), rounded<br>st integer                                    | 20                        | Energy efficiency class  | E            |  |  |  |
| dicating if it refe<br>a sphere (360º)            | s flux (фuse), in-<br>ers to the flux in<br>, in a wide cone<br>arrow cone (90º) | 2 500 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000        |  |  |  |
| On-mode pow<br>pressed in W                       | ver (P <sub>on</sub> ), ex-  | 20,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |  |  |  |
| (P <sub>net</sub> ) for CLS, 6                    | candby power expressed in W the second dec-                                      | -                         | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |  |  |  |
| Outer dimen-                                      | Height   | 165                       | Spectral power dis-  | See image    |  |  |  |
| sions without                                     | Width  | 165                       | tribution in the   | in last page |  |  |  |
| separate con-<br>trol gear, light-<br>ing control | Depth  | 90                        | range 250 nm to 800<br>nm, at full-load  |              |  |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |      |                              |       |  |  |  |
|--|------|------------------------------|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>                                   | -    | If yes, equivalent power (W) | -     |  |  |  |
|  |      | Chromaticity coordi-         | 0,380 |  |  |  |
|  |      | nates (x and y)              | 0,380 |  |  |  |
| Parameters for LED and OLED light sources:                                 |      |                              |       |  |  |  |
| R9 colour rendering index value  | 5    | Survival factor              | 1,00  |  |  |  |
| the lumen maintenance factor   | 0,96 |                              |       |  |  |  |

(a)'-': not applicable; (b)'-': not applicable;

