

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ULTRALUX

**Supplier's address:** Boriana Ltd, Treti Mart 12, 5370 Dryanovo Gabrovo, BG

**Model identifier:** PSW5CCT

## Type of light source:

|                                                     |                         |                                 |      |
|-----------------------------------------------------|-------------------------|---------------------------------|------|
| Lighting technology used:                           | LED                     | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | External flexible cable |                                 |      |
| Mains or non-mains:                                 | MLS                     | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No                      | Envelope:                       | -    |
| High luminance light source:                        | No                      |                                 |      |
| Anti-glare shield:                                  | No                      | Dimmable:                       | No   |

## Product parameters

| Parameter                                                                                                                                      |        | Value                | Parameter                                                                                                                                                  | Value                   |
|------------------------------------------------------------------------------------------------------------------------------------------------|--------|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| General product parameters:                                                                                                                    |        |                      |                                                                                                                                                            |                         |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                  |        | 5                    | Energy efficiency class                                                                                                                                    | F                       |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |        | 500 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 or 4 000 or 6 500 |
| On-mode power ( $P_{on}$ ), expressed in W                                                                                                     |        | 5,0                  | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                               | 0,00                    |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                |        | -                    | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 80                      |
| Outer dimensions without separate control gear, lighting control                                                                               | Height | 95                   | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page  |
|                                                                                                                                                | Width  | 95                   |                                                                                                                                                            |                         |
|                                                                                                                                                | Depth  | 30                   |                                                                                                                                                            |                         |

|                                                                                                                         |      |                                       |                |  |
|-------------------------------------------------------------------------------------------------------------------------|------|---------------------------------------|----------------|--|
| parts and non-lighting control parts, if any (millimetre)                                                               |      |                                       |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | -    | If yes, equivalent power (W)          | -              |  |
|                                                                                                                         |      | Chromaticity coordinates (x and y)    | 0,380<br>0,380 |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |      |                                       |                |  |
| R9 colour rendering index value                                                                                         | 5    | Survival factor                       | 0,90           |  |
| the lumen maintenance factor                                                                                            | 0,94 |                                       |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |      |                                       |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 0,60 | Colour consistency in McAdam ellipses | 5              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)     | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 0,5  | Stroboscopic effect metric (SVM)      | 0,2            |  |

(a) '-': not applicable;

(b) '-': not applicable;



**EPREL registration number:** 2709244

Model placed on the Union market.



<https://eprel.ec.europa.eu/qr/2709244>

**Supplier:** BORIANA LTD (Manufacturer)

**Website:** [ULTRALUX.BG](https://ultralux.bg)

**Customer care service:**

**Name:** Boriana Ltd

**Website:** [ultralux.bg](https://ultralux.bg)

**Email:** [sales@ultralux.bg](mailto:sales@ultralux.bg)

**Phone:** +35967674433

**Address:**

Treti Mart 12  
5370 Dryanovo  
Bulgaria