## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: ULTRALUX

Supplier's address: -

## Model identifier: L2S1216427

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS			
Light source cap-type	Gu5.3					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Yes			
Product parameters						

Parameter		Value	Parameter	Value			
General product parameters:							
Energy consur mode (kWh/10 up to the neare	00 h), rounded	4	Energy efficiency class	F			
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone nrow cone (90º)	320 in Wide cone (120°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	2 700			
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00			
(P <sub>net</sub> ) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen-	Height	52	Spectral power dis-	See image			
sions without	Width	50	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	50	range 250 nm to 800 nm, at full-load				

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	40
		Chromaticity coordi- nates (x and y)	-
Parameters for directional light s	ources:	I	
Peak luminous intensity (cd)	-	Beam angle in de- grees, or the range of beam angles that can be set	120
Parameters for LED and OLED lig	ht sources:		
R9 colour rendering index value	-	Survival factor	0,90
the lumen maintenance factor	0,95		

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;