

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** ULTRALUX

**Supplier's address:** -

**Model identifier:** MLPG4540

**Type of light source:**

|   |      |                                 |     |
|---|------|---------------------------------|-----|
| Lighting technology used:                           | LED  | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | -    |                                 |     |
| Mains or non-mains:                                 | NMLS | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | No   | Envelope:                       | -   |
| High luminance light source:                        | No   |                                 |     |
| Anti-glare shield:                                  | No   | Dimmable:                       | No  |

## Product parameters

| Parameter  | Value                    | Parameter  | Value   |
|--|--------------------------|--|---|
| <b>General product parameters:</b>   |                          |  |   |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 5                        | Energy efficiency class  | G   |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 290 in Narrow cone (90°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000   |
| On-mode power ( $P_{on}$ ), expressed in W   | 4,5                      | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00  |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                        | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 80  |
| Outer dimensions without separate control gear, lighting control   | Height                   | 12   | Spectral power distribution in the range 250 nm to 800 nm, at full-load |
|  | Width                    | 600  |   |
|  | Depth                    | 24   |   |
|  |                          |  | See image in last page  |

|   |      |  |        |
|---|------|--|--------|
| parts and non-lighting control parts, if any (millimetre) |      |  |        |
| Claim of equivalent power <sup>(a)</sup>                  | -    | If yes, equivalent power (W)                                       | -      |
|   |      | Chromaticity coordinates (x and y)                                 | -<br>- |
| <b>Parameters for directional light sources:</b>          |      |  |        |
| Peak luminous intensity (cd)                              | -    | Beam angle in degrees, or the range of beam angles that can be set | 90     |
| <b>Parameters for LED and OLED light sources:</b>         |      |  |        |
| R9 colour rendering index value                           | -    | Survival factor  | 0,90   |
| the lumen maintenance factor                              | 0,96 |  |        |

(a): not applicable;

(b): not applicable;