


DATA SHEET

INDIRECT LED DOWNLIGHT SQUARE, 12W, 4200K, 220V, NEUTRAL LIGHT, SMD2835

ILDS1242



DESCRIPTION

The reflected light is the most preferred solution for general lighting - this is the light that does not come directly from the light source but is reflected by a wall, ceiling or special reflector of the luminaire. It provides a uniform light in the room and does not create shadows of contrast, and the light is soft and no dazzle. Suitable solution for indoor lighting such as offices, shops, residential buildings, hotels, restaurants. As an advantage can be highlighted easy installation, uniform and even light.

APPLICATION

- For home use
- For kitchen use
- For office and shop use

Light technical information

- Rated luminous flux: 820 lm
- Flicker: <5%
- Color Rendering Index (CRI): >80
- Beam angle: 120 °
- Correlated Color Temperature (CCT): 4200 K

Electrotechnical information

- Voltage: 220-240 V AC
- Frequency: 50-60 Hz
- Power factor: >0.5
- Power: 12 W
- Driver: Built-in, non-dimmable

Basic information

- Type of protection: IP20
- Working temperature: -10°C ÷ +40 °C
- Mounting hole: 131/131 mm
- On/Off Cycles: >15 000
- Lumen Maintenance L80B50: >30 000 h
- Dimensions: 145/145/43 mm
- Warranty: 3 years