DATA SHEET



PROFESSIONAL LED FLEXIBLE STRIP SMD3528, 4.8W/M, NEUTRAL WHITE, 24V DC, 60LEDS/M, 5M, NON-WATERPROOF

PN3560N





DESCRIPTION

The professional UltraLux LED strip series are made of quality components and materials. They have improved light output compared to standard series. The double-sided adhesive tape is a 3M brand, which guarantees quality assembly. The warranty period is longer (3 years) compared to strips in the standard series (1 year). The supply voltage is 24 V DC, which is twice as large as that of the standard series, this is a prerequisite for smaller losses and reduced voltage drop.

Note:

- When installing, it is advisable to use aluminum profiles for cooling, especially for large capacities.
- Minimum Order Quantity 5m (1 Roll).

Light technical information

Rated luminous flux: 400 lm/mLEDs per meter: 60 LEDS/m

• Color Rendering Index (CRI): ≥80

• Beam angle: 120 °

• Correlated Color Temperature (CCT): 4200 K

SDCM: <5LED type: 3528

Electrotechnical information

• Voltage: 24V DC

Power per meter: 4.8 W/m
PCB type: Double layer
Voltage drop: <5 %/5m
PCB thiknes: 3 oz

Basic information

• Type of protection: IP20

Working temperature: -10 ÷ +40°C
Dimensions: 5 meters / 8 mm

• Lumen Maintenance L80B50: 50 000 h

• Energy class: A+

