DATA SHEET



LED HIGH BAY WITH DIMMABLE DRIVER 0-10V, 100W, 5000K, 100-277V AC, IP65

LIKX10050



DESCRIPTION

A new model LED industrial lamp (highbay) with 100W power, innovative construction, excellent efficiency, compact size, and lighter weight. It is offered in neutral 5000K light with the following advantages:

- Innovative construction with central heat dissipation cavity, ensuring better cooling and longer diode life;
- Very high efficiency > 150 lm/W;
- High quality LED chips Osram Duris;
- The emitted light is flicker free;
- The customer can choose from 60°, 90° and 120°, polycarbonate diffusers with UV-protection (sold separately);
- Dimmable driver ZH POWER a sure guarantee for reliable operation and long exploitation period. ZH is an established high-tech brand with proven quality;
- Controlling signal is 0-10V DC and allows dimming from 0% to 100%;
- Built-in overvoltage protection 4 kV;
- Powder-coated aluminum housing that ensures mechanical strength and excellent diode cooling;
- A ring and a bracket (included in the set) allow a choice of mounting;
- Compact size and lighter weight;
- High ingress protection rate IP65;
- High impact resistance rate IK08.
- Long warranty 5 years;

Application:

- Lighting of working areas;
- Lighting of factories;
- Lighting of warehouses;
- Industrial lighting;
- Interior and exterior lighting

Electrotechnical information



• Power: 100 W

Voltage AC: 100-277 VFrequency: 50-60 HzPower factor: >0.95

• Driver: With built-in 4 kV surge protection according to IEC 61000-4-5

• Dimmable: yes

Light technical information

• Efficiency: 150 lm/W

• Rated luminous flux: 15000 lm

• Correlated Color Temperature (CCT): 5000

• Color Rendering Index (CRI): >80

Beam angle: 90/120 °
LED type: OSRAM

Basic information

• Protection rating: IP65

• Impact protection rate: IK08

• Working temperature range: -20 °C ÷ +50 °C

• On/Off cycles: >30000

• Lumen Maintenance LM80: >50000 h

Height: 180 mmDiameter: 250 mmWarranty: 5 years

