ux.bg

DATA SHEET



PROFESSIONAL LED FLEXIBLE STRIP 9.6W/M, 2700K, 24V DC, 120LEDS/M, IP20

PN35120W



DESCRIPTION

The professional UltraLux LED strip series are made of quality components and materials. They have improved light output compared to standard series. The double-sided adhesive tape is a 3M brand, which guarantees quality assembly. The warranty period is longer (3 years) compared to strips in the standard series (1 year). The supply voltage is 24 V DC, which is twice as large as that of the standard series, this is a prerequisite for smaller losses and reduced voltage drop.

Note:

- When installing, it is advisable to use aluminum profiles for cooling, especially for large capacities.
- Minimum Order Quantity 5m (1 Roll).

APPLICATION

- Home use
- Offices

Electrotechnical information

• Power per meter: 9.6 W/m

• Voltage DC: 24 V

• Dimmable: PWM and voltage dimming

Light technical information

• LEDs per meter: 120 LEDS/m

• Correlated Color Temperature (CCT): 2700 K

• Color Rendering Index (CRI): >80

Beam angle: 120 °
LED type: SMD3528

• luminous flux per meter: 1000 lm/m

• Type of light: warm white

Basic information

• Protection rating: IP20

• Working temperature range: -10 °C ÷ +40 °C

• Lumen Maintenance LM80: 50000 h

Starting time: <0.2 sec
Strip width: 10 mm
Strip length: 5 m



