DATA SHEET



LED DOWNLIGHT FOR BUILDING-IN 7W, 4000K, 220V, WARM LIGHT, WHITE, SMD2835, IP44

LLV740



DESCRIPTION

Suitable solution for indoor lighting such as offices, shops, residential buildings, hotels, restaurants. The LED downlight is suitable for bathrooms and damp rooms. This is due to the high degree of dust and moisture protection IP44.

APPLICATION

- For home use
- For kitchen use
- For office and shop use
- For bathroom

Light technical information

- Rated luminous flux: 470 lm
- Flicker: <5%
- Color Rendering Index (CRI): >80
- Beam angle: 120 °
- Correlated Color Temperature (CCT): 4000 K
- Photometric file (.LDT): Yes

Electrotechnical information

• Voltage: 220-240 V AC • Frequency: 50/60 Hz • Power factor: >0.5 • Power: 7 W

• Class: II

• Driver: Build-in, non-dimmable

Basic information

• Type of protection: IP44

• Working temperature: -10 $^{\circ}$ C ÷ +40 $^{\circ}$ C

• Mounting hole: Ø70 mm • On/Off Cycles: >15 000

• Lumen Maintenance L80B50: >30 000 h

• Dimensions: Ø85/37 mm

• Color: White • Warranty: 2 years

